

1-4 NV5000 α 1B

項目 Item		NV5000 α 1B/40	NV5000 α 1B/50
移動量 Travel	X 軸移動量 (テーブル左右) X-axis travel (Longitudinal movement of table)	mm (in.)	1020 (40.15)
	Y 軸移動量 (サドル前後) Y-axis travel (Cross movement of saddle)	mm (in.)	510 (20.07)
	Z 軸移動量 (主軸頭上下) Z-axis travel (Vertical movement of spindle head)	mm (in.)	510 (20.07)
	テーブル上面から主軸端面までの距離 Distance from table surface to spindle gage plane	mm (in.)	150 - 660 (5.90 - 25.98)
テーブル Table	テーブル作業面の大きさ Working surface	mm (in.)	1320 × 600 (51.96 × 23.62)
	テーブルの最大積載質量 Table loading capacity	kg (lb.)	1200 (2640)
	テーブル上面の形状 Table surface configuration	18 mm T 溝 6 本 Six 18 mm (0.7 in.)-wide T-slots	
主軸 Spindle	主軸最高回転速度*1 Max. spindle speed*1	min ⁻¹	14000 [20000] 8000 [15000]
	主軸変速レンジ数 Number of spindle speed ranges	段 Step	1
	主軸テーパ穴 Spindle taper hole		No. 40 No. 50
	主軸軸受内径 Spindle bearing inner diameter	mm (in.)	65 (2.55) 100 (3.94)
送り速度 Feedrate	早送り速度 Rapid traverse rate	mm/min (ipm)	X, Y, Z: 42000 (1653)
	切削送り速度 Cutting feedrate	mm/min (ipm)	1 - 6000 (0.04 - 236) [1 - 42000 (0.04 - 1653)*2]
	ジョグ送り速度 Jog feedrate	mm/min (ipm)	0 ~ 1260 < 15 段 > 0 - 1260 (0 - 50) < 15 Steps >

項目 Item		NV5000 α 1B/40	NV5000 α 1B/50
ATC 装置 ATC unit	ツールシャンク形式 Tool shank type	BT-40 [CAT-40, HSK A-63]	BT-50 [CAT-50, C6, HSK A-100]
	フルスタッド形式 Retention knob type	森精機専用 90° [MAS-I (45°), MAS-II (60°), C6, HSK] 90° for Mori Seiki [MAS-I (45°), MAS-II (60°), C6, HSK]	
	工具収納本数 Tool storage capacity	30 [60, 90]	30 [60]
	工具最大径 <隣接工具あり> Max. tool diameter <with adjacent tools>	mm (in.)	80 (3.14) 120 (4.72)
	工具最大径 <隣接工具なし> Max. tool diameter <without adjacent tools>	mm (in.)	125 (4.92) 240 (9.45)
	工具最大長さ Max. tool length	mm (in.)	300 (11.81) 350 (13.78)
	工具最大質量 Max. tool weight	kg (lb.)	8 (17.60) [12 (26.40)] 20 (44.0)
	工具選択方式 Method of tool selection	テクニカルメモリランダム Technical memory random method (Shorter route fixed address method)*3	
	主軸用電動機 (30 分/連続) Spindle drive motor (30 min./continuous rating)	kW (HP)	22/18.5 (30/25), 15/11 (20/15)*4
	送り軸用電動機 Feed motors	kW (HP)	X, Y: 4.0 (5.5), Z: 5.5 (7.5)
電動機 Motors	潤滑用電動機 Lubricant pump motor	kW (HP)	0.017 (0.02)
	クーラント用電動機 (50 Hz/60 Hz) Coolant pump motor (50 Hz/60 Hz)	kW (HP)	0.635 (0.84)*5, 1.04 (1.38)*6
	機内コンベヤ用電動機 In-machine chip conveyor motor	kW (HP)	0.2 × 2 (左右) 0.2 (0.26) × 2 (Left/right disposal)
	冷却油用電動機 Cooling oil pump motor	kW (HP)	3.4 (4.53)
	電源 (連続定格) Electrical power supply (continuous rating)	kVA (HP)	41.3, 32.7*4 45.3
	空気圧源 Compressed air supply	MPa (psi), L/min (gal)	0.5 (72.50), 200 (52.80) <ANR>*7
	潤滑油タンク容量 Lubricant tank capacity	L (gal)	2.0 <主軸、ボールねじ> 2.0 (0.52) <Spindle/Ball nut>
機械の大きさ Machine size	クーラントタンク容量 Coolant tank capacity	L (gal)	275 (72.6)*8, 735 (194.04)*9, 740 (195.36)*10
	機械の高さ Machine height	mm (in.)	2603 (102.48) 2640 (103.94)
	所要床面の大きさ Required floor space	mm (in.)	2788 × 2710 (109.76 × 106.69) 3088 × 2636 (121.57 × 103.78)
	機械質量 Mass of machine	kg (lb.)	6960 (15312) 7310 (16082)